



FOSCA FC-150

Formaldehyde Scavenger

FOSCA FC-150 is an advance formulated liquid catcher that performs by penetrating into wood and disintegrating formaldehyde that was emitted from wood products such as Plywood, Medium Density Fiberboard, Particle Board and etc.

- ✓ Superior penetration into wood surface, thus can get even coating volume.
- ✓ Achieved F***, F****, CARB-P2, E0, SE0 standard.
- ✓ Not effected to wood products quality such as bonding, moisture resistant, water resistant and etc.
- ✓ Stable result even after long period of time.

APPLICATION

Coat or Spray on Veneer and Wood Panel.

STORAGE

Store in cool and dry protected from the heat. The products should be labeled and properly marked location.

PACKAGING

200L drum or 1000kg IBC tank

SPECIFICATIONS

| | |
|------------|--------------|
| Appearance | Clear liquid |
| Odour | None |

RECOMMENDED COATING VOLUME

Direct apply on wood with below coating volume:

| Coating area | Coating Volume (g/ft ²) | Coating Volume (g/m ²) |
|-----------------------|-------------------------------------|------------------------------------|
| Face (Top surface) | 3 - 5 | 30 - 50 |
| Back (Bottom surface) | 3 - 5 | 30 - 50 |

Coating Application Area:

1. Apply on Veneer:

Before Dryer

2. Apply on Wood Panel:

After Hotpress. Please check the moisture content (M.C) of wood panel surface, if M.C > 14%, need to go through dryer to reduce the M.C <14% to achieved standard and prevent moldy issue.