

LOG SEALANT LS-1

Keep Your Log Fresh

LOG SEALANT LS-1 is a elastomeric water based log sealant that protects the ends of green logs and lumber from checking and splitting. It is a high performance and economical choice for customers. When applied properly to the freshly cut ends, it can prevents log end checking, protecting your logs and extending the life of woods.

- ✓ **Reduce the water loss from log to keep the freshness**
- ✓ **Can be applied to all wood species**
- ✓ **Prevents stain caused by fungi**
- ✓ **Water based, non-toxic formula**

SURFACE PREPARATION

Log ends or lumber area to be coated must be clear from dirt and debris. Apply LOG SEALANT LS-1 as quickly as possible after end trimming, to achieve the highest level of protection against end checking and degrade.

APPLICATION

1. Apply LOG SEALANT LS-1 using a brush or roller.
2. Apply as much LOG SEALANT LS-1 as the log or lumber will hold, until it begins to drip slightly.
3. If LOG SEALANT LS-1 does not begin to drip, you may not be applying enough sealer.

STORAGE

LOG SEALANT LS-1 should be stored in cool and dry place and away from heat. Close the lid tightly after use.

PACKAGING

25kg/pail

CLEANING

Use soapy water to clean the equipment. Solvent cleaner are not recommended or needed.

SPECIFICATIONS

Appearance	: Viscous liquid
Colour	: Yellow (Color can be made upon request)
Solid Content	: 60 % - 70 %
Density	: 0.800 - 0.850 g/ml
Coverage	: 1 - 2 m ² /kg



Apply the log sealant until it started to drip slightly to make sure that the coating volume is enough.



With LOG SEALANT LS-1



Without LOG SEALANT LS-1